

TALKSWITCH TELEPHONE SYSTEMS

TALKSWITCH 484vs

A full-featured, all-in-one telephone system that handles both traditional and VoIP telephony.

- VOICE OVER IP ENABLED
- BUILT-IN SIP SERVER
- VOICEMAIL
- CELL/PAGER/E-MAIL NOTIFICATION OF NEW MESSAGES
- AUTO ATTENDANTS
- REMOTE EXTENSIONS
- AUTO FAX DETECTION
- DIAL-BY-NAME DIRECTORY
- AUTOMATIC ROUTE SELECTION
- MUSIC ON HOLD
- USER-CONFIGURABLE
- CALL FORWARD
- CALL CASCADE
- CALL DETAIL RECORD LOGGING
- RING GROUPS
- CALL BACK/CALL BRIDGE
- CALL HOLD/PARK/PICKUP
- CALL TRANSFER
- CALL CONFERENCE
- INTERCOM
- PUBLIC ADDRESS
- CALL QUEUE
- MODE SCHEDULING
- HOLIDAY MODE
- CALL SCREENING
- DISTINCTIVE RING
- USES STANDARD AND IP PHONES
- EXPANDABLE
- LAN CAPABILITY
- FLASH UPGRADEABLE
- LOCAL & REMOTE MANAGEMENT
- EXPANDABLE MEMORY
- UNIFORM CALL DISTRIBUTION

TALKSWITCH 484vs

The TalkSwitch 484vs is a hybrid telephone system capable of handling both traditional telephone and Voice over IP calls. Using VoIP allows calls from one location to be routed over the Internet to a VoIP-equipped TalkSwitch (or VoIP gateway) in another location, eliminating long distance charges. The TalkSwitch 484vs also directly integrates with VoIP service provider networks.


TalkSwitch 484vs systems include all the features that we're known for. Voicemail, auto attendants, innovative remote extensions and sophisticated call handling helps businesses look big, reduce communications costs and stay connected everywhere. With standard connections for fast and easy installation and free PC configuration software, TalkSwitch 484vs set-up and changes are a snap.

CAPACITY

- 4 lines in
- 8 analog or IP local extensions
- 10 remote extensions
- 4 VoIP trunks
- 9 auto attendants
- 28 voice mailboxes

Like all TalkSwitch systems, the TalkSwitch 484vs is ready to grow. It comes with capacity for **4 traditional telephone lines, 4 VoIP trunks and 8 local extensions**, but you can increase capacity any time by networking it with other TalkSwitch units (including the 48-CA, 48-CVA and any VS units). The maximum capacity of TalkSwitch systems is **16 traditional phone lines, 16 VoIP trunks and 32 local and 40 remote extensions**.

CONNECTIONS



Extensions: 8 standard 2-pin RJ-11 ports — TalkSwitch 484vs units support up to 8 standard analog telephones and fax machines or IP telephones.

PA Output: 1/8" mono phone jack to connect the TalkSwitch 484vs to a PA system to announce calls, or to a local speaker to monitor incoming calls and voicemail

Audio Input: 1/8" mono phone jack allows connection of standard audio devices (CD players, radio or PC soundcards) for music or messages on hold. Can also play a .wav file stored on the TalkSwitch.

Available From:

Power Systems
 877-774-1521
 www.powersystemsdirect.com

Platinum Talkswitch Megastore

Ethernet Connection: RJ-45 10BaseT Ethernet connection for LAN networking and management and access to 4 VoIP trunks.

Memory Card Slot: The TalkSwitch 484vs comes with 30 minutes of built-in voicemail and auto attendant memory, which can be upgraded by up to 9 hours.

Incoming Lines: 4 standard 2-pin RJ-11 ports; support for Caller ID and distinctive ringing.

USB Port: TalkSwitch 484vs units can optionally be connected to a PC via a USB port for configuration. Ethernet cable and configuration software is included. The system does not need to be connected to a PC to function.

Power Source: 120 VAC, 60 Hz — In / 16 VAC, 1.5 A — Out. AC adapter included.

GROW YOUR OWN WAY

TalkSwitch is designed to provide a smooth evolutionary path that protects your investment and meets your needs for future growth. Up to 4 TalkSwitch 484vs units can be networked on a single LAN, meaning that when your business is ready to grow, your telephone system is ready to grow right along with it.

FREE SOFTWARE UPDATES. YES, FREE.

Software: TalkSwitch comes with free user-friendly Windows-based configuration software. We’re continually adding features and functionality to our software, and we don’t charge for updates.

Warranty: The TalkSwitch 484vs is covered by a limited one-year warranty.

TECHNICAL SPECIFICATIONS

System		Ringing sensitivity	45 volts RMS @ 20 Hz
Analog trunks	4	REN	0.7B
VoIP trunks	4	Longitudinal balance	69 dB
Analog extension interfaces	8	Signal level	-10 dB
USB interface	1	Distinctive ring supported	Yes
LAN interface	RJ-45 Ethernet (10BaseT)	Caller ID support	FSK, all lines
Memory expansion	1, 2, 4.5 and 9 hour memory cards		

Power-failure line to extension jacks: Extension 4 connects to Line 1

Analog extension interface

Connector type	RJ-11, 2-pin
Trunk type	Loop start
Interface impedance	600 ohms
Loop range	0–600 ohms
Hook flash supported	Yes
On-hook voltage	35 volts
Off-hook loop voltage source	35 volts
Off-hook loop current	23 mA to 40 mA
Dial tone level	-2.4 dBm
Ringing voltage	90 volts RMS
Ringing frequency	20 Hz – true sine wave
Total ringing load	5 REN

Analog trunks

Connector type	RJ-11, 2-pin
Trunk type	Loop start
Interface impedance	Configurable
	600 ohms, 600 complex
	900 ohms, 900 complex
Ringing impedance	3,900 ohms

VoIP features

- Embedded SIP server and user agents
- Integrated registrar
- Can use external SIP servers as required
- RTP
- G.711 µ-law/A-law, G.726 (32 Kbps), G.729a
- G.168 echo cancellation
- VAD, silence suppression
- Adaptive jitter buffer
- Packet loss concealment
- Fax tone detection

Dimensions (H x W x L)

Metric	51.6 mm x 203.2 mm x 213.4 mm
Imperial	2.03" x 8" x 8.4"

Weight

Metric	0.81 kg
Imperial	1.77 lbs

Regulatory Approvals

CE ACTA TIA/EIA/IS-968A and FCC Part 68
 Industry Canada CS-03
 FCC Part 15B, Industry Canada ICES-003
 Power adapter complies with UL and CSA

About TalkSwitch

TalkSwitch® designs and develops award-winning phone systems for small, multi-location and franchise businesses. Since its establishment in 1990, TalkSwitch has dedicated itself to developing PBXs and IP PBXs that tens of thousands of small businesses across North America rely on. With a growing global network of resellers, distributors and partners, TalkSwitch phones and phone systems are changing the way small businesses communicate.

© TalkSwitch 2006

